



Domestic users / Sensors / Motion Detectors / IS 140-2

IS 140-2

Information copy

The classic detector, now with even more class. Infrared motion detector IS 140-2, for indoors and out, ideal for targeted detection close to the building, 140° angle of coverage, reach up to 14 m, selectable time and twilight threshold, sensor turns through 90° and tilts through 180° for exact adjustment of the detection zone.



Details

1000w

1000 W max.

3 JAHRE
HERSTELLER
GARANTIE
steinel.de/garantie

manufacturer warranty steinel.de/garantie



2 - 2000 lux



IP54



ideal 2 m



max. 14 m



180° horizontal, 90° vertical



infrared sensor 140°



energy saving



8 sec - 35 min



UV-protected material



Optional corner wall mount bracket

Technical specifications IS 140-2 White

European Article Number (EAN)	4007841608910
Dimensions(w x h x d):	70 x 86 x 95 mm
Model	Movement sensor
Voltage	230-240 V/50 Hz
Sensor type	Passive infrared
Application	indoors and outdoors
Installation	Wall
Output	Max. 1000 W, max. 6 fluorescent lamps / LED lamps, C < 132 µF
Detection angle	140° with sneak-by protection
Capability of masking out individual segments	Yes
Swivelling range	180 °
Tilting range	90 °
Reach	14 m max. (temperature-stabilised)
Response value luminosity	2-2000 lx
Teach-function for response value luminosity	No
Time setting	8 sec. - 35 min.
Degree of protection (IP)	IP54
Protection class	II
Version	White

Application

outdoors and indoors

for targeted detection of movement in areas close to the building